

HOW TO USE Pro-Series INTERFACING from FASHION SEWING SUPPLY

PRO-WOVEN Standard SEW IN Interfacing #1 Light-Weight, does not shrink at all. However, you can pre-treat this interfacing in the usual manner: Soak in warm water, lift gently, and hang to dry. To Use "Pro-Woven Standard", cut and apply as you would any regular SEW-IN interfacing.

PRO-WOVEN Fusible Interfacing is very stable and its fusible resin is very stable and specially applied. **It does not shrink.** However, you may pre-treat in the usual manner: soak in warm water, lift gently, and hang to dry. To Apply--

1. Cut the "Pro-Woven Fusible" to the desired size and shape.
 2. Place the "Glue Side" down onto the wrong side of the fabric.
 3. Cover with a thin press cloth.
 4. Using Medium-High heat (High Wool to Cotton setting), Press using Firm pressure AND LOTS OF STEAM for 20 seconds before moving your iron to the next section. DO NOT slide the Iron.
 5. Turn over and repeat the same pressing (#4) from the right side of your fabric piece, making sure you use a press cloth.
- ENSURE SUCCESS BY USING LOTS OF STEAM! **Then press briefly again with a DRY IRON to dry and seal completely.**

PRO-WEFT FUSIBLE Interfacing is a light weight, softly brushed and very supple weft-insertion interfacing especially suitable for "soft" tailoring and also can be used to completely underline tailored or casual jackets. "Pro-Weft Fusible" is also a perfect choice for soft shaping of shirt collars and cuffs of mid to heavyweight shirting fabrics like denim and hemp. It stabilizes the fabric, providing wonderful body yet preserves the fabric's drape. **It does NOT shrink.** Apply Pro-Weft the same way as Pro-Woven Fusible (above), BUT use the "Wool" setting on your steam iron.

PRO-SHEER ELEGANCE FUSIBLE Interfacing is a very lightweight knit interfacing with controlled stretch in all directions. **It does NOT shrink.** It has wonderful drape and is suitable for all knits and lightweight woven fabrics.

1. Cut the "Pro-SHEER ELEGANCE Fusible Interfacing" to the desired size and shape.
 2. Place the "Glue Side" down onto the WRONG side of the fabric.
 3. Cover with a lightweight press cloth.
 4. IF your fabric is washable, mist the press cloth VERY LIGHTLY with water. IF your fabric is VERY delicate, use a DRY press cloth.
 5. Pro-SHEER ELEGANCE can be fused at an iron temperature from "silk" to "low wool". It will depend on your fabric, start with a low temp, and go a little higher if you need to.
- Fuse the interfacing to the fabric using firm even pressure for 20 seconds.
6. Turn over and repeat pressing from the right side, making sure to use a press-cloth.

The finished garment should be laundered delicately in cool water, laid flat to dry, or dried in a low temperature dryer. The garment may also be dry-cleaned. *IF YOUR FABRIC IS WASHABLE AT HIGHER TEMPERATURES, YOU CAN FUSE "PROSHEER ELEGANCE" WITH STEAM, then wash/dry on "warm" laundry settings. *****

PRO-TRICOT Fusible Interfacing is a lightweight fusible knit interfacing that is perfect for knit fabrics of all kinds. It also can be used to completely underline fabrics for tailoring applications and can be fused to LEATHER. It *may* shrink a little bit, so you can may pre-treat this interfacing in the usual manner, or steam-shrink it during application (preferred method) --

1. Cut the "Pro-Tricot Fusible" to the desired size and shape.
2. Place the "Glue Side" down onto the wrong side of the fabric.
3. With iron set to a "Low Wool" setting, hold it *Just Above* the interfacing and lightly steam the "Pro-Tricot Fusible". The interfacing may shrink slightly.
4. Cover with a press cloth and Fuse the interfacing to the fabric using firm, even pressure for a full 20 seconds.
5. Turn over and repeat the same pressing from the right side of your fabric piece, using a press cloth.

PRO-TAILOR DELUXE Fusible Interfacing comes to us from the very finest and famous Fashion workrooms. **It is washable and may also be dry-cleaned.** This unique WARP-insertion *Woven* Fusible Interfacing is made for tailoring applications. It is slightly crisp, yet its special weave gives it a flexible hand. **It Does NOT Shrink.** To Apply--

1. Cut the "Pro-Tailor Deluxe" to the desired size and shape.
2. Place the "Glue Side" down onto the wrong side of the fabric.
3. Cover with a press cloth, then Using Medium-High heat (Wool setting range), PRESS with STEAM using Firm pressure for 20 seconds before moving your iron to the next section. DO NOT slide the iron.
4. Turn over and repeat the same pressing (#3) from the right side of your fabric piece. Use a press cloth.
5. If a crisper/heavier weight is desired, fuse another layer of Pro-Tailor Deluxe on top of the first, repeating step1-5.

IMPORTANT- Wash garments made with ANY Fusible interfacing on cool to warm laundry settings ONLY.